PT-058: Underwater Case System Chart

Waterproof Compact Cameras
Tough TG-5
RED

Waterproof Compact Cameras
Tough TG-5
BLK

Antireflective Ring
POSR-053
(provided with the PT-058)

Weight
PWT-1AD

Weight
PWT-1BA

Short Arm
PTSA-02

Short Arm
PTSA-03

Electronic Flash
UFL-3
- Withstand pressure water depth: 75 m

Underwater optical fiber cable
PTCB-E02

Optical fiber cable Adapter
PFCA-03
(provided with the PT-058)
- Dual-flash compatible

Diffuser for UFL-3
UFLDP-4
(provided with the UFL-3)

Arm & Adapter
(other company's products)

Bracket
(other company's products)

Underwater Case for Tough TG-5
PT-058
- Withstand pressure water depth: 45 m

Step-up Ring
PSUR-03
- ø52mm-67mm

Underwater approx. 0.6X (underwater angle of view approx. 100°)

Underwater Wide Conversion Lens
PTWC-01
- Change the digital camera setting. Press the OK button to display the live control, then selected "PTWC-01" under "Accessory Setting" with arrow pads or control dial. Then press the OK button.
- Even if the setting has been changed, the four corners of the image may be darkened when the zoom is used.
- When used on land, the four corners of the image get cropped.

Underwater Macro Conversion Lens
PTMC-01
- The tip is provided with a 67 mm diameter filter thread for stacking with other lens filter or lens.

LCD hood
PFUD-08
(provided with the PT-058)

Lens Cap
PRLC-14
(provided with the PT-058)

Hand strap
PST-EP01
RED

Consumables for PT-058 Underwater Cases

Silicone grease
PSOLG-2
(5 g)

Silicone grease
PSOLG-3
(40 g)

Silica gel
SILCA-5S
(1 g x 5 pieces)

O-ring for PT-058
POL-058
(provided with the PT-058)

Maintenance Set
PMS-02